

162

DEPENDENT RESURVEY PORTION EAST BOUNDARY, T.21 S., R.63 E.

Chains

79.73

Proportionate point, on steep rocky E. slope,

Set an iron post, 3 ft. long, 2 ins. in dia., over cross cut in solid rock, and supported by a large mound of stone to top, for cor. of secs. 25 and 36, T.21 S., R.63 E. only, with brass cap marked

T21S

S25

S36

R63E

1931

Land, mountainous; general N. exposure and drainage.

Soil, coarse and shallow rocky loam; 4th rate.

No timber.

Undergrowth, creosote and chaparral.

INDEPENDENT RESURVEY NORTH BOUNDARY OF T22 S., R.63½ E.

INDEPENDENT RESURVEY SUPERSEDING SURVEY

EXECUTED BY T. A. MAGEE, U. S.

DEPUTY SURVEYOR IN 1883.

From the cor. of Tps. 21 and 22 S., Rs. 63½ and 64 E., heretofore described.

West, bet. secs. 1 and 36.

Across draw, over rough mountainous land through creosote and chaparral undergrowth.

1.50 Leave draw, bears N.30°E. and S.30°W.; ascend steep and rocky E. slope.

4.90 S. point of rocky spur; gradually descend.

7.25 Rocky draw, heads about 4 chs. N.70°W. and drains S.70°E.; ascend steep rocky NE. slope.

16.70 Rocky ridge spur, 290 ft. above Tp. cor., bears N. and S.; a spur projects W. about 1 ch. distant to the N.; descend abruptly 85 ft. to

19.65 Head of draw, drains SW.; thence along rocky S. slope.

23.50 S. point of rocky spur from the NE.; descend rocky SW. slope 195 ft. to

30.80 Junction of draws from the SE. and S.; drains N.20°W.; ascend abruptly 165 ft. over rocky NE. slope.

38.25 Rocky spur, projects NW.; descend rocky SW. slope 70 ft.

40.00 Point for ¼ sec. cor. falls on steep rocky outcrop where cor. cannot be set.

40.10 Set an iron post, 3 ft. long, 1 in. in dia., 15 ins. in the ground on solid rock and supported by a large mound of stone for witness cor. to the ¼ sec. cor., with brass cap marked