

INDEPENDENT RESURVEY OF SUBDIVISION, T. 21 S., R. 65 E.

Chains

35.28 On general N. slope, 60 ft. below bench; intersect the fifth standard parallel south, R. 65 E., East, 28.38 chs. dist. from the standard cor. of secs. 33 and 34, T. 20 S., R. 65 E., which is an iron post, 2 ins. diam., firmly set, marked and witnessed as described in book "A" of this group.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap marked

T20S R65E

S34

S4

T21S R65E

C C

1931

Mound of stone, 3 ft. base, 2 ft. high, S. of cor. ^{raise a}

Land, rough and broken, with a general southwesterly and northeasterly exposure and drainage.

Soil, gravelly, sandy, and rocky, with clay; conglomerate formation.

Undergrowth, shadscale, creosote, and greasewood.

No timber.

From the cor. of secs. 15, 16, 21, and 22.

East, on auxiliary base line, bet. secs. 15 and 22.

Descend abrupt NE. slope of broken land, through scattered short undergrowth.

2.50 Base of abrupt descent at W. edge of wash, 30 ft. below cor., bears N. and S.; thence across wash which drains S.

6.50 The E. edge of wash, bears N. and S.; ascend abrupt W. slope.

11.10 Spur, 200 ft. above wash, projects S.; descend abrupt SE. slope.

16.20 Draw, 110 ft. below spur, drains SW.; ascend gradual W. slope.

27.00 Spur, 100 ft. above draw, projects SW.; descend gradual SE. slope.

32.00 Shallow draw, drains S. 30° E.; continue gradual descent.

33.00 Low spur, projects S.

40.00 On gradual SE. slope, 85 ft. below spur at the 27.00 chs. point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S15

 $\frac{1}{4}$

S22

1931