

256

INDEPENDENT RESURVEY OF SUBDIVISION, T. 22 S., R. 63 E.

Chains

- 79.96 The cor. of secs. 1, 2, 11, and 12, 200 ft. below spur.
Land, broken and mountainous, with a general northwesterly exposure and drainage.
Soil, shallow gravel and rock; 3rd rate.
Undergrowth, creosote and cacti.
No timber.
-
- N. 0°10' E., bet. secs. 1 and 2, on true line.
- Over rolling mountainous land through scattered undergrowth.
- 9.00 Low rocky spur, projects S. 70° W.
- 15.40 Small wash, 20 lks. wide, drains W., about 8.00 chs. dist., thence NW.; ascend abrupt rocky SW. slope.
- 19.80 Slope changes from the SW. to the W.
- 29.15 Top of rocky point on W. slope of spur which projects N, 140 ft. above wash; thence along W. slope near top of spur.
- 37.10 Bottom of swale, drains SW.; continue along W. slope.
- 38.00 Small rocky spur, projects W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$
 S2 | S1
 1931
- raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- 44.45 Rocky spur, 50 ft. above the $\frac{1}{4}$ sec. cor., projects NW.
- 46.00 Begin gradual descent over rocky N. slope.
- 55.70 Wash, 30 lks. wide, 200 ft. below spur, drains N. 30° W. from the SE.; ascend abrupt rocky SW. slope.
- 62.60 Small rocky spur, 90 ft. above wash, projects W., about 5.00 chs. dist. to end; descend N. slope.
- 67.40 Rocky draw, 100 ft. below spur, drains W. and heads 2.00 chs. to the E.; ascend abrupt rocky S. slope.
- 68.80 Top of ledge, 25 ft. high, on spur, 40 ft. above draw, projects W.; descend N. slope.
- 73.85 Head of draw, 100 ft. below spur, drains S. 60° W.
- 77.70 Low rocky spur, projects S. 60° W. and bears E., 1.00 chs. dist. to rocky spur which projects N.; descend along rocky W. slope.
- 84.30 Intersect the S. bdy. of sec. 35, T. 21 S., R. 63 E., S. 89°27' W., 4.32 chs. dist. from the cor. of secs. 35 and 36, T. 21 S., R. 63 E., which is an iron post, 2 ins.