

INDEPENDENT RESURVEY OF SUBDIVISION OF T.22 S., R.63 1/2 E.

Chains

46.92 Intersect E. bdy. of sec. 25, T.22 S., R.63 E.

Set an iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground on solid rock with a stone, 12x8x6 ins., marked with a cross (+) on one face deposited alongside, and supported by a large mound of stone to top for the closing cor. of secs. 25 and 36, with brass cap marked

T22S	T22S	
S25	S25	C
R63E	S36	C
	R63 1/2 E	

1931

From this cor., the 1/4 sec. cor. on the E. bdy. of sec. 25, T.22 S., R.63 E., bears S.0°11'W., 10.58 chs. distant; an iron post, 1 in. in dia., firmly set, and marked and witnessed as described in the official record, Book "B", this group.

Closing cor. stands in bottom of small draw draining N.20°W. from the SE.

Land, rolling and broken; general NW. exposure and drainage.

Soil, coarse gravelly loam and rocky; 3rd. and 4th. rates.

No timber.

Undergrowth, creosote and chaparral.

From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., which is an iron post, 2 ins. in dia., firmly set, and marked and witnessed as described in the official record, Book "B", this group.

West, on true line bet. secs. 24 and 25.

Over rolling land draining W., through creosote and chaparral undergrowth.

1.60 Spur, projects SW.; gradually descend 105 ft. to

34.15 Wash, 1 ch. wide, drains SW.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 1/4 sec. cor., with brass cap marked

S24

S25

1931

raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

46.63 Intersect E. bdy. of sec. 24, T.22 S., R.63 E.

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for closing cor. of secs. 24 and 25, with brass cap marked