

BOULDER CANYON PROJECT FEDERAL RESERVATION BOUNDARY

Chains

- 70.75 High rocky spur, 245 ft. above draw, projects SW. for about 4 chs., thence W.; descend abruptly over N. slope.
- 75.65 Draw, 115 ft. below spur, drains NW. for about 2 chs., then W.; gradually ascend.
- 76.30 Low spur, projects W. about 1 ch. distant to end; descend
- 77.10 Draw, drains SW.; ascend abruptly over S. slope.
- 80.00 Intersect line bet. secs. 18 and 19, T.22 S., R.64 E.

Set an iron post, 3 ft. long, 3 ins. in dia., 12 ins. in the ground on solid rock and supported by a large mound of stone for the 20th. Mile Cor. and closing cor. of secs. 18 and 19, T.22 S., R.64 E., with brass cap marked

	T22S	R64E
C	S18	20M
		BCP
C	S19	FR

1931

From this cor., the cor. of secs. 13, 18, 19, and 24, T. 22 S., Rs. 63 1/2 and 64 E., bears West, 1.98 chs. distant; for description of cor. see Book "B", this group.

Cor. stands on steep S. slope 70 ft. above draw.

Land, mountainous; general W. exposure and drainage.

Soil, sandy and gravelly clay loams and rocky of limestone and volcanic formation; 4th. rate.

No timber.

Undergrowth, scattering creosote 1 to 4 ft. high and short shadscale and chaparral.

North, on the 21st. Mile.

Abrupt ascent over steep rocky E. slope of mountainous land through scattering creosote, shadscale and chaparral undergrowth.

- 2.65 Rocky ridge, 85 ft. above mile cor., bears N.80°W. and S.80°E. about 1 ch., then NE.; abrupt descent over N. slope.

7.25 Head of draw, 110 ft. below ridge, drains W.; descend along W. slope.

9.25 Spur, 30 ft. below head of draw, projects N.70°W.; descend abruptly over N. slope.

- 18.85 Wash, 20 lks. wide, 3 ft. deep, in draw, 205 ft. below spur, drains W. for about 4 chs., then NW.; ascend abruptly over S. slope.

- 25.65 Spur, 115 ft. above draw, projects S.70°E.; low saddle in spur, bears S.70°E. about 1 ch. distant; descend