

BOULDER CANYON PROJECT FEDERAL RESERVATION BOUNDARY

Chains

80.00

On gentle NW. slope, 240 ft. below spur.

Set an iron post, 3 ft. long, 3 ins. in dia., 28 ins. in the ground for the 23rd. Mile Cor., with brass cap marked

23M

BCP

FR

1931

raise a mound of stone, 5 ft. base, 3½ ft. high, E. of cor.

Land, rough and broken mountains; general N. exposure.

Soil, clay, gravelly and rocky loams of limestone and volcanic formation; 3rd. and 4th. rates.

No timber.

Undergrowth, scattered creosote 1 to 4 ft. high and short shadscale and chaparral.

North, on the 24th. Mile.

Gradually descend over mountainous land through creosote shadscale and chaparral undergrowth.

1.66

Intersect N. bdy. sec. 6, T.22 S., R.64 E., East, 1.98 chs. distant from the cor. of Tps. 21 and 22 S., Rs. 63½ and 64 E., described in Book "B", this group; closing cor. of secs. 6 and 31 established at this point; for description of same see Book "B", this group.

3.35

Junction of washes from the SW. and S.30°E., drain N.; gradually descend along wash.

10.75

Leave wash, 35 ft. below mile cor., drains N.10°W.; thence along rough and broken W. slope.

15.05

Top of ascent on W. slope, 40 ft. above wash, bears E. and W.; gradually descend along W. slope.

27.80

Small rocky spur, 65 ft. below top of ascend, projects NW. about 1 ch. distant to end; descend 50 ft. to

30.75

Recross wash noted at 10.75 chs., drains N.E.; ascend 30 ft. to

31.55

Small rocky spur, projects SE. about 80 lks. distant to end at wash; gradually descend along gentle E. slope.

40.00

Point for the 23½ Mile Cor. falls on small rocky point where it is impracticable to establish cor.

41.10

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground on solid rock and supported by a mound of stone for witness cor. to the 23½ Mile Cor., with brass cap marked

23½M

BCPFR

WC

1931