

BOULDER CANYON PROJECT FEDERAL RESERVATION BOUNDARY

Chains

31½ M
BCPFR
1931.

raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

Cor. stands at foot of slope on W. edge of bottom of draw bearing N. and S.; thence across draw.

49.25 Wash, 10 lks. wide, 3 ft. deep, 65 ft. below bench, drains S.5°W.; leave draw, bears N. and S., gradually ascend over W. slope.

59.40 Spur, 90 ft. above draw, projects S.5°W.; descend.

70.45 Wash, 10 lks. wide, 3 ft. deep, in draw, 55 ft. below spur, drains S.10°W.; gradually ascend.

76.28 N. 26 lks. from the tangent, intersect the W. bdy. of T.21 S., R.65 E., South, 1.83 chs. distant from the cor. of secs. 13, 18, 19, and 24; for description of cor. see Book "B", this group; closing cor. for secs. 19 and 24 established at this point and also described in Book "B".

In order to test the alinement of the tangent line carried forward to this point, I sight on a flag on the W. bdy. of T.21 S., R.65 E. and which bears South as determined by observations on Polaris during the survey of the Tp. bdy., and deflect an angle of 90°04' to the right to a flag on my tangent line about ½ mile distant to the west. The reduced bearing of the tangent is N.89°56'W. which indicates that the line has been carried forward satisfactorily.

80.00 N. 26 lks. from the tangent.

Set an iron post, 3 ft. long, 3 ins. in dia., 28 ins. in the ground for the 32nd. Mile Cor., with brass cap marked

32 M
BCPFR
1931

raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.

Cor. stands on gentle NW. slope, 50 ft. above wash.

Land, rolling and broken clay, sand, and gypsum hills; general S. drainage.

Soil, clay, sandy, gravelly, and gypsum; 3rd. and 4th. rates.

No timber.

Undergrowth, scattering creosote, shadscale and cacti.