

12.8 DEPENDENT RESURVEY NORTH BOUNDARY OF T.8 N., R.31 E.

Chains

ended

T9N R31E
S31 S32
NAD S5
T8NR31E

1931

raise a

mound of stone, 5 ft. base, $3\frac{1}{2}$ ft. high, N. of cor.

78.65 Center line of the Goldfield branch of the S.P.Ry., bears N.65°52'W. and S.65°52'E.

79.75 Telegraph line, bears N.65°52'W. and S.65°52'E.

81.06 The original cor. of secs. 5, 6, 31, and 32 which is a quartz stone, 16x12x12 ins., standing in an old deeply embedded mound of stone, and marked with 5 notches on E. and 1 notch on W. edge.

At cor. point, I reset the corner monument 12 ins. in the ground, marked with 5 notches on E. and 1 notch on W. edge, for cor. of secs. 5 and 6, T.8 N., R.31 E., and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

Land, gently rolling valley with general S. exposure and drainage.

Soil, deep, loose coarse sand, gravelly and rocky; 2nd. to 4th. rates.

No timber.

Undergrowth, shadscale, greasewood, weeds and sand grass.

S.88°26'W., bet. secs. 6 and 31.

Over gently rolling valley through short undergrowth.

35.78 Westing of 40.00 chs. from the cor. of secs. 31 and 32, T.9 N., R.31 E.

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for $\frac{1}{4}$ sec. cor. sec. 31, T.9 N., R.31 E., with brass cap marked

S31

1931

raise a

mound of stone, 4 ft. base, 3 ft. high, N. of cor.

37.87 The original $\frac{1}{4}$ sec. cor., which is a limestone, 14x12x8 ins., lying on the ground, marked dimly $\frac{1}{4}$ on one face, and witnessed by a few scattered and deeply embedded stones around cor.

At cor. point,

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground and bury original cor. alongside for $\frac{1}{4}$ sec. cor. sec. 6, T.8 N., R.31 E., with brass cap marked