

Chains

for cor. of secs. 1 and 12, with brass cap mkd.

T 11 N	
R45E	R46E
S 1	
S12	S 7

1938

from which

A pinon pine, 4 ins. diam., bears N. 32 3/4° W., 94 lks. dist., mkd. T 11 N R 45 E S 1 B T.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

39.76

The original cor. of secs. 1, 6, 7 and 12, which is a sandstone, 6x8x18 ins., loosely set in a small mound of stone, mkd. with 5 grooves on S. and 1 groove on N. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original stone, deposited at the base, for cor. of secs. 6 and 7, with brass cap mkd.

T 11 N	
R45E	R46E
S 1	
S 6	S 7

1938

from which

A juniper, 7 ins. diam., bears N. 24 1/2° E., 222 lks. dist., mkd. T 11 N R 46 E S 6 B T.

A pinon pine, 4 ins. diam., bears S. 21 3/4° E., 74 lks. dist., mkd. T 11 N R. 46 E S 7 B T.

Land, rolling mountainous.

Soil, sandy rocky and gravel; 3rd rate.

Timber, pinon pine and juniper; undergrowth, sagebrush and a fair growth of grass.

N. 1° 10' E. on west boundary sec. 6.

Over rolling mountainous land, through scattering timber and dense undergrowth, desc.

- 2.10 Dry wash, 10 lks. wide, 4 ins. deep, drains N. 70° E.; asc. 10 ft.
- 5.40 Top of low spur, projects E.; desc. 15 ft.
- 7.80 Small wash, drains E.; asc. 15 ft.
- 13.40 Top of low spur, projects N. 70° E.; desc. 20 ft.
- 17.00 Wash, drains N. 70° E.; asc. 15 ft.
- 19.70 Top of low spur, projects S. 80° E.; desc. 10 ft.
- 21.00 Wash, drains E.; asc. 20 ft.
- 24.60 Top of low spur, projects E.; desc. 20 ft.
- 28.10 Wash, drains S. 60° E.; asc. 25 ft.