

INDEPENDENT RESURVEY OF THE
2nd STAN. PAR. N., S. BDY. T. 11 N., R. 48 E.

Chains	S. 80° E.; asc. 10 ft.
67.60	Point of low spur, projects SE.; desc. 30 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 7 ins. in the ground to bedrock, with a granite stone, 3x6x8 ins., mkd. X, deposited at the base, and in a mound of stone to top, for standard cor. of secs. 35 and 36, with brass cap mkd.
	S C T11N R48E S35 S36 <hr style="width: 50%; margin: auto;"/> 1938
	Land, mountainous. Soil, sandy clay loam, shallow and very rock; 3rd rate. Timber, scattering aspen, pinon pine, juniper and mahogany, undergrowth, sagebrush, willow and a fair growth of grass.
	East, along the S. bdy. of sec. 36, by solar method. Over mountainous land, through scattering timber and undergrowth, desc. 30 ft.
3.10	Wash, drains S. 20° W.; asc. 40 ft.
8.00	Point of spur, projects S.; desc. 10 ft.
11.00	Wash, drains S.; asc. 40 ft.
16.20	Point of spur, projects S.; desc. 25 ft.
21.10	Wash, drains S.; desc. 10 ft.
26.40	Point of spur, projects S.; desc. 10 ft.
27.70	Head of wash, drains S.; asc. 30 ft.
30.30	Point of spur, projects S.; desc. 150 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bed rock and in a mound of stone to top, for standard 1/4 sec. cor., with brass cap mkd.
	S C 1/4 S 36 <hr style="width: 50%; margin: auto;"/> 1938
	from which
	A pinon pine, 10 ins. diam., bears N. 60 1/4° E., 37 lks. dist., mkd. 1/4 S 36 S C B T.
	A pinon pine, 7 ins. diam., bears N. 62° W., 61 lks. dist., mkd. 1/4 S 36 S C B T.
	Desc. 200 ft. over broken E. slope.
58.10	Junction of ravines, from N. 50° W. and N. 20° E.; thence ravine course S. extends 2.00 chs. dist.; thence course S. 70° E.; asc. 25 ft.
59.80	Point of spur, projects S.; desc. 25 ft.
62.40	Ravine, course S. 70° E.; asc. 45 ft.