

INDEPENDENT RESURVEY OF A PORTION OF THE 2ND STAN. PAR. N., S. BDY.
T. 11 N., R. 49 E.

Chains	
34.00	Top of spur, slopes S. 80° E.; desc. 10 ft.
37.80	Ungraded road, bears N. 80° W. and S. 80° E.
38.40	Greenmonster Creek, 4 lks. wide, clear water, 8 ins. deep, course S. 75° E.; asc. 15 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock and in a mound of stone to top, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S C $\frac{1}{4}$ S 31 <hr/> 1938
	from which
	A pinon pine, 12 ins. diam., bears N. 56 $\frac{1}{4}$ ° W., 40 lks. dist., mkd. $\frac{1}{4}$ S 31 S C B T.
	A pinon pine, 10 ins. diam., bears N. 19 $\frac{1}{2}$ ° W., 15 lks. dist., mkd. $\frac{1}{4}$ S 31 S C B T.
	All trace of the original standard $\frac{1}{4}$ sec. cor., has disappeared. Asc. 210 ft. over NE. slope.
57.00	Top of spur, projects S. 40° E.; desc. 15 ft.
58.60	To point of intersection with a line projected South 17.41 chs. dist. from the standard cor. of T. 11 N., R. 48 E., an iron post 3 ins. diam., described in field notes of the Independent Resurvey of the 2nd Stan. Par. N., thru R. 48 E., resurveyed under this group.
	Set an iron post, 3 ft. long, 3 ins. in diam., 25 ins. in the ground and in a mound of stone to top, for standard cor. of T. 11 N., R. 49 E., with brass cap mkd.
	S C T11N R49E S 31 <hr/> 1938
	from which
	A pinon pine, 12 ins. diam., bears N. 11 $\frac{1}{2}$ ° E., 49 lks. dist., mkd. T 11 N R 49 E S 31 S C B T.
	A pinon pine, 12 ins. diam., bears N. 49 $\frac{1}{4}$ ° E., 59 lks. dist., mkd. T 11 N R 49 E S 31 S C B T.
	From this standard cor.; the original standard cor. of Ts. 11 N., Rs. 48 and 49 E., bears N. 84° 33' W., 16.98 chs. dist., which is a juniper post, greatly decayed, 4 ft. long, 4 ins. sq., firmly set in mound of stone, mkd. dimly legible with scribe markings but not readable. All traces of pits have disappeared.
	At point for cor.,
	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, with broken pieces of the original post, deposited at the base and in a mound of stone, for witness point, for the identification of the original standard cor. of Tps. 11 N., Rs. 48 and 49 E., with brass cap mkd.
	W P <hr/> 1938