

124

EAST BOUNDARY OF T. 11 N., R. 48 E.

Chains	
25.80	Top of spur, projects S. 80° E.; desc. 360 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 1 only, with brass cap mkd.
	$\frac{1}{4}$ S 1 1938
	from which
	A pinon pine, 9 ins. diam., bears S. 74 3/4° W., 198 lks. dist., mkd. $\frac{1}{4}$ S B T.
	A pinon pine, 7 ins. diam., bears N. 33° W., 180 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.
40.90	Clear Creek, 3 lks. wide, 4 ins. deep, course S. 80° E.; asc. 485 ft. over rocky rugged SW. slope.
58.55	Cor. of Ts. 11 and 12 N., R. 49 E.; an iron post 3 ins. diam., mkd. and witnessed as described in the field notes of the survey of T. 12 N., R. 49 E., executed under Group 244, at the same time as, and in connection with T. 11 N., R. 49 E., this group. Asc. 75 ft.
61.60	Top of spur, projects S. 85° E.; desc. 185 ft.
68.70	Ravine, course S. 80° E.; asc. 260 ft.
75.45	Intersect the N. bdy. of T. 11 N., R. 48 E.
	Set an iron post, 3 ft. long, 3 ins. diam., 16 ins. in the ground to bedrock and in a large mound of stone to top, for cor. of Ts. 11 and 12 N., R. 48 E., with brass cap mkd.
	T12N R48E T12N S36 R49E S 1 S31 T11N 1938
	from which
	A pinon pine, 8 ins. diam., bears S. 26 1/2° W., 36 lks. dist., mkd. T 11 N R 48 E S 1 B T.
	A pinon pine, 10 ins. diam., bears N. 51 1/4° W., 50 lks. dist., mkd. T 12 N., R. 48 E S 36 B T.
	Land, rough rugged mountainous. Soil, sandy loam, shallow and rocky; 3rd rate Timber, pinon pine, juniper and mahogany; undergrowth, sagebrush and a fair growth of grass.
	DEPENDENT RESURVEY OF A PORTION OF SUBDIVISIONAL LINES OF T. 11 N., R. 49 E.
	Reestablishment of a portion of section lines executed by D. H. Barker and W. W. Skinner, Deputy Surveyors in 1875.
	Beginning at the standard cor. of secs. 32 and 33, on the S. bdy. of the tp.
	N. 0° 39' E., on true line bet. secs. 32 and 33.
	Over rolling mountainous land, through scattering undergrowth, asc. gradually.
30.00	Wash, drains S. 70° E.; asc. 15 ft.