

SUBDIVISIONS OF T. 11 N., R. 49 E.

Chains

East, on true line bet. secs. 17 and 20.

Over rolling mountainous land, through scattering timber and dense undergrowth, desc. 125 ft.

32.10 Wash, drains SE.; asc.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 17
 $\frac{1}{4}$

S 20

1938

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.00 Wash, drains SE.; asc.

50.20 Dim road, bears NW. and SE.; desc. 40 ft.

76.50 Ungraded road, bears NW. and SE.; desc. 30 ft.

82.04 Intersect the W. bdy. of sec. 16.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 17 and 20, with brass cap mkd.

T11N R49E	
CC	S17
	S20
	S16

1938

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

The cor. of secs. 16 and 21, hereinbefore described, bears S. $2^{\circ}07'$ W., 4.81 chs. dist.

Land, rolling mountainous.

Soil, sandy loam, shallow and rocky; 3rd rate.

Timber very scattering and scrub juniper and pinon pine; undergrowth sagebrush and a fair growth of grass.

From the cor. of secs. 17, 18, 19 and 20.

West, on true line bet. secs. 18 and 19.

Over rolling mountainous land, through scattering timber and dense undergrowth, asc. 60 ft.

13.10 Top of spur, projects SE.; desc. 15 ft.

16.50 Wash, drains S. 40° E.; leave rolling mountainous land, enter mountainous land, bears NE. and SW.; asc. 210 ft.

35.00 Top of spur, projects SE.; desc. 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 18

$\frac{1}{4}$
S 19

1938

from which

A pinon pine, 6 ins. diam., bears S. $59\frac{1}{4}^{\circ}$ E., 33 lks. dist.,