

INDEPENDENT RESURVEY OF A PORTION OF THE 3RD STAN. PAR. N.,
THRU R. 45 E.

Chains

From the cor., the original standard $\frac{1}{4}$ sec. cor., which is a weathered stake, 2x2x40 ins., indistinctly scribed, and lying on a faint mound of earth, bears S. 6° E., 74 lks. dist. I destroy all trace of old corner.

53.00 Dry wash, drains N. 60° W.; asc. 40 ft. over W. slope.

67.80 Low spur, projects NW., desc. along gentle NE. slope.

74.00 Hillside drain, course N. 20° W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, over a cross X, cut on solid bedrock, and in a large mound of stone to top of post, for stan. cor. of secs. 35 and 36, with brass cap mkd.

SC

T16N R45E

S35 | S36

1937

of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound

Land, rolling.

Soil, sandy to gravelly loam; 2nd and 3rd rate.

Undergrowth, shadscale, rabbit brush, greasewood.

No timber.

Grazing, fair.

East, on true line, along the S. bdy. of sec. 36.

Over broken rolling to hilly land thru medium dense low undergrowth.

1.70 Draw, drains N. 70° W.; asc. 130 ft. over broken NW. slope.

9.50 Spur, projects NW.; desc. along a broken N. slope.

13.90 Small spur, projects N.

17.20 Main draw, drains N. 15° W.; asc. 60 ft. over W. slope.

25.20 Minor spur, projects N. 40° W.

32.20 Ravine, drains N. 20° W.; asc. 120 ft. over W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, over a cross X, cut at exact cor. point on solid bedrock, and in a large supporting mound of stones to top, for stan. $\frac{1}{4}$ sec. cor., with brass cap mkd.

SC

 $\frac{1}{4}$ S 36

1937

From this cor., the old stan. $\frac{1}{4}$ sec. cor., which is badly weathered post, 2x2x40 ins., indistinctly scribed, bears S. 21° 50' W., 2.28 chs. dist. No trace of pits or mound. I destroy all evidence of the original corner.

42.40 Spur, projects NW.; desc. across broken N. slope.

51.30 Draw, drains NW.; continue over rolling NW. slopes.

68.00 Minor spur, projects N.