

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONS IN T. 16 N., R. 45 E.

Chains

Reestablishing the survey executed by A.J. Hatch, D. H. Barker, and E. L. Bridges, Deputy Surveyors, in 1873. From the stan. cor. of secs. 33 and 34 on the S. bdy. of the Tp., N., 0° 31' E., on true line along the E. bdy. of sec. 33.

Over rolling land along a gentle W. slope thru medium dense low undergrowth.

38.62

Point for the 1/4 sec. cor. of sec. 34.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 34 only, with brass cap mkd.

1/4 S 34

1937

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.

40.12

Proportionate distance, no trace of the original 1/4 sec. cor. being found,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 33 only, with brass cap mkd.

1/4 S 33

1937

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

78.62

The point for the closing cor. of secs. 27 and 34, hereinafter described.

80.24

The original cor. of secs. 27, 28, 33 and 34, which is an aspen post, 2x2x40 ins., faintly scribed on two faces, and lying on a slight mound of earth.

At point for cor., in center of mound,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with old cor. at base, for the cor. of secs. 28 and 33 only, with brass cap mkd.

T16N R45E

S28

S27

S33

1937

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Land, rolling. Soil, sandy and gravelly loam; 3rd rate. Undergrowth, shadscale, greasewood. No timber.

N. 2° 28' E., on true line along E. bdy. of sec. 28 (south half mile).

Over gentle rolling W. slopes thru medium dense low undergrowth.

26.40

Road, bears N. 41° E. and S. 41° W.

Point for the 1/4 sec. cor. of sec. 27.

38.41

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for