

172

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONS OF T. 16 N., R. 45 E.

Chains 74.39 Point for the closing cor. of secs. 10 and 11, hereinafter described.

80.00 Record distance, Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2 and 3 only, with brass cap mkd.

T16N R45E

S 3 | S 2

S11

1937

raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.

Land, rolling.

Soil, sandy to gravelly loam; 3rd rate.

Undergrowth, shadscale, greasewood, rabbitbrush.

No timber.

From the cor. of secs. 2 and 3,

N. 0° 19' W., bet. secs. 2 and 3,

40.00 Record distance, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base of post, for the 1/4 sec. cor., with brass cap mkd.

S3 | S2

1937

79.70 The cor. of secs. 2, 3, 34 and 35 on the N. bdy., previously described.

Land, rolling.

Soil, sandy to coarse gravelly loam; 3rd rate.

Undergrowth, greasewood, shadscale, rabbitbrush.

No timber.

COMPLETION OF THE SUBDIVISION OF T. 16 N., R. 45 E.

From the stan. cor. of secs. 35 and 36 on the S. bdy.

N. 0° 01' W., bet. secs. 35 and 36,

Over rolling and broken NW. slopes thru medium dense low undergrowth.

3.00 Small ravine, drains NW.

10.20 Spur, slopes N. 60° W.; desc. 150 ft. over NW. slope.

40.00 On south edge of broad, shallow dry wash, draining N. 75° W.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S35 | S36 ✓

1937