

SURVEY OF THE N. BDY. OF T. 16 N., R. 45 $\frac{1}{2}$ E.

Chains


West, on true line, bet. secs. 2 and 35,

Desc. over gently rolling NW. slopes thru medium dense low undergrowth.

22.68 Intersect the E. bdy. of Sec. 12, T. 16 N., R. 45 E., North, 12.75 chs. distant from the $\frac{1}{4}$ sec. cor. of Sec. 12 which is an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the field notes of T. 16 N., R. 45 E.

At point of intersection.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 2 and 35, Ts. 16 and 17 N., R. 45 $\frac{1}{2}$ E., with brass cap mkd.



1937

raise a mound

of stone, 3 ft. base, 2 ft. high, E. of cor.

Land, rolling.

Soil, gravelly clay loam; 3rd rate.

Undergrowth, shadscale, greasewood.

Grazing, poor.

SURVEY OF THE SUBDIVISIONS IN T. 16 N., R. 45 $\frac{1}{2}$ E.

From the Std. cor. of secs. 35 and 36 on the S. bdy. of the Tp.,
N. 0° 01' W., bet. secs. 35 and 36.

Over mountainous land thru medium dense low undergrowth and medium heavy small timber. Asc. 80 ft. along a broken W. slope.

7.00 Spur, slopes N. 70° W.; desc. along a broken W. slope.


19.60 Low spur, slopes N. 60° W.; desc. 120 ft. over NW. slope.

22.80 Small seepage spring on line.

26.90 Drain, course N. 60° W.; continue desc. along an irregular W. slope.

35.60 Spur, slopes N. 75° W.; desc. 130 ft. over abrupt N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A pinon pine, 10 ins. diam., bears S. 63 $\frac{1}{2}$ ° E., 67 lks. dist., mkd. $\frac{1}{4}$ S36 BT.