

214

SURVEY OF THE SUBDIVISIONS OF T. 16 N., R. 45 $\frac{1}{2}$ E.

Chains


Over rolling land thru medium dense low undergrowth.

4.70 Shallow drain, course N. 75° W.

22.76 Intersect the W. bdy. of Tp.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 11 and 14, with brass cap mkd.



1937

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this clos. cor., the $\frac{1}{4}$ sec. cor. of Sec. 24, T. 16 N., R. 45 E., bears South, 14.53 chs. dist, and is an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the field notes of T. 16 N., R. 45 E., executed under this group.

Land, rolling.

Soil, coarse gravelly to rocky loam; 3rd rate.

Undergrowth, sagebrush, shadscale, greasewood.

No timber.

Grazing, fair to poor.

From the cor. of secs. 11, 12, 13 and 14.

N. 0° 01' W., bet. secs. 11 and 12.


Over rolling land thru medium dense low undergrowth. Over broken W. slope.

17.30 Drain, course N. 80° W.

30.60 Drain, course S. 80° W.

37.20 Spur, slopes NW.; desc. N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite rock, 3x3x6 ins., mkd. X, deposited at base of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Desc. over rolling and irregular NW. slopes.

47.40 Old road in dry wash, 20 lks. wide, 1 ft. deep, draining W., bears SE. and W.

60.70 Draw, drains N. 60° W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.