

258

SUBDIVISION OF T. 16 N., R. 46 E.

Chains	
36.40	Spur, slopes SW.; desc. over gradual W. slope thru scattering timber.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S3 \mid S2 \checkmark \\ 1937 \end{array}$
	from which
	A juniper, 16 ins. diam., bears N. $41\frac{1}{4}^{\circ}$ E., 340 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
	A pinon pine, 14 ins. diam., bears S. $37\frac{1}{4}^{\circ}$ W., 268 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	From this cor., the junction of U. S. Highway No. 50 and the Potts-Monitor valley road bears N. $44^{\circ} 05'$ W., about 15 miles distant.
61.10	Desc. 80 ft. over broken W. slope. Draw, drains W.; asc. 50 ft. over S. slope.
66.70	Top of abrupt slope, continue over gentle S. slope, thru very scattering timber and medium dense, low undergrowth.
78.10	Intersect the N. bdy. of Tp.
	At point of intersection
	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock and in a large mound of stone to top of post, for closing cor. of secs. 2 and 3, with brass cap mkd.
	$\begin{array}{c} T17N \ R46E \\ S34 \\ \hline S3 \mid S2 \\ CC \\ T16N \ R46E. \\ 1937 \end{array}$
	from which
	A pinon pine, 12 ins. diam., bears S. 39° E., 655 lks. dist., mkd. T16NR46ES2 CC BT.
	A pinon pine, 6 ins. diam., bears S. $79\frac{1}{4}^{\circ}$ W., 77 lks. dist., mkd. T16NR46ES3 CC BT.
	From this closing cor., the cor. of secs. 34 and 35 bears East, 2.19 chs. dist.
	Land, rolling mountain top. Soil, shallow coarse rocky loam; 3rd rate. Undergrowth, sagebrush. Timber, pinon pine, juniper, mahogany. Grazing, good.
	From the stan. cor. of secs. 33 and 34 on the S. bdy. of the Tp., N. $0^{\circ} 02'$ W., bet. secs. 33 and 34,
	Over mountainous land, thru medium dense timber and scattering undergrowth. Asc. 280 ft. over broken S. slope.
22.00	W. edge of rounded, rocky knoll. Desc. 210 ft. over N. slope.