

SUBDIVISION OF T. 16 N., R. 46 E.

Chains

A pinon pine, 10 ins. diam., bears S. 32° W., 85 lks. dist.,
mkd. $\frac{1}{4}$ S10 BT.

57.40 Draw, drains N W., continue over rolling and broken SW. slopes, thru scattering timber.

68.40 Spur, slopes NW.

77.20 Draw, drains SW.; asc. 120 ft. over SE. slope.

79.94 The cor. of secs. 3, 4, 9 and 10.

Land, rough mountainous.

Soil, shallow rocky loam; 3rd rate.

Undergrowth, sagebrush.

Timber, pinon pine, juniper.

Grazing, fair to poor.

N. $0^{\circ} 02'$ W., on true line bet. secs. 3 and 4.

Over rolling and broken land thru scattering timber and undergrowth.

Asc. 140 ft. over S. slope.

11.80 Spur, slopes S. 30° W.

19.20 Draw, drains S. 80° W.

25.60 Spur, slopes S. 70° W.; desc. over rolling NW. slopes.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock and in a large mound of stone to top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S4 | S3

1937

from which

A juniper, 5 ins. diam., bears S. $11 \frac{3}{4}^{\circ}$ E., 74 lks. dist.,
mkd. $\frac{1}{4}$ S3 BT.

A juniper, 10 ins. diam., bears S. $7 \frac{1}{2}^{\circ}$ W., 115 lks. dist.,
mkd. $\frac{1}{4}$ S4 BT.

43.70 Spur, slopes S. 50° W., desc. 220 ft. over NW. slope.

74.00 Draw, drains N. 85° W.; asc. 40 ft. over SW. slope.

78.06 Intersect the N. bdy. of Tp.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.

T17N R46E

S33

S4 | S3

CC

T16N R46E

1937

from which

A pinon pine, 6 ins. diam., bears S. $33 \frac{3}{4}^{\circ}$ E., 175 lks. dist.,