

COMPLETION OF RANGE LINE BETWEEN TS. 16 N., Rs. 46 and 47 E.

313

Chains

mkd. $\frac{1}{4}$ S24 BT.

44.00

Spur, slopes SE.; desc. 70 ft. over E. slope.

52.00

Shallow drain, course E.; asc. 70 ft. over rocky SW. slope.

63.70

Spur, slopes S. 80° E.; desc. 160 ft. over abrupt N. slope.

73.00

Draw, drains N. 60° E.; continue along gentle E. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T16N R47E

S13 S18

S24 S19

1937

from which

A pinon pine, 4 ins. diam., bears N. 37 $\frac{1}{2}$ ° E., 162 lks. dist., mkd. BT only.

A pinon pine, 4 ins. diam., bears S. 52° W., 171 lks. dist., mkd. BT only.

A pinon pine 10 ins. diam., bears N. 27 $\frac{1}{2}$ ° W., 138 lks. dist., mkd. S 13 BT only.

Land, broken, rocky foothills.

Soil, coarse, rocky loam; 3rd rate.

Undergrowth, sagebrush, greasewood, buck brush.

Timber, pinon pine, juniper.

Grazing, good.

North, bet. secs. 13 and 18. (S. $\frac{1}{2}$ mile)

Over broken rolling E. slope, through medium dense undergrowth and scattering timber; desc. 70 ft.

38.40

Dry wash, 10 lks. wide, 1 ft. deep, drains NE.

40.00

The reestablished $\frac{1}{4}$ sec. cor. of secs. 13 and 18, previously described.DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONS OF T. 16 N.,
R. 47 E.

Commence at the stan. cor. of secs. 31 and 32, on the S. bdy. of the tp., previously described.

Thence

N. 0° 20' E., on true line, along the W. bdy. of sec. 32.

Over rolling land, through medium dense low undergrowth.

12.10

Dry wash, 10 lks. wide, 2 ft. deep, course S. 70° E.

21.50

Dry wash, 20 lks. wide, 1 ft. deep, course N. 70° E.

39.84

Proportionate distance

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, over a granite rock, 3x4x9 ins., mkd. X, deposited at the base of