DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONS OF T. 16 N., R. 47 E.

318

Chains	From the cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the tp., previously described.
	S. 88° 02' E., on true line bet. secs. 7 and 18.
	Over rolling land, through scattering low undergrowth; desc. 160 ft. over SE. and E. slopes to wash.
.38.30	Dry wash, 12 ft. wide, 1 ft. deep, course N. 50° E.
39.09	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a porphyry rock, 2x4x6 ins., mkd. X, deposited at base of post, for 4 sec. cor., with brass cap mkd.
	S 7
	west printed and the state of t
t	\$ 18
*	1937
	Continue descent of rolling E. slope.
63,20	Dry wash, 20 1ks. wide, 2 ft. deep, course N. 60° E.
78.45	The reestablished cor. of secs. 7, 8, 17 and 18.
	Land, rolling.
	Soil, coarse, gravelly and rocky loam; 3rd rate. Undergrowth, sagebrush, white sage, greasewood. No timber.
	Grazing, fair.
* ** *********************************	COMPLETION OF THE SURVEY OF THE SUBDIVISIONS OF T. 16 N., R. 47 E.
	From the cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp.
	East, on true line, bet. secs. 30 and 31.
	Over rolling land, through medium dense undergrowth; desc. 100 ft. over E. slope.
36.10	Draw, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, with a granite rock, 4x4x6 ins., mkd. X, deposited at base of post
	and in a large supporting mound of stone to top, for a sec. cor.
	s 30
	\$ s 31
	1937
63.70	Broad shallow wash, drains N. 70° E.
68.50	Old wood road, bears N. 50° W. and S. 70° E.
70.77	Intersect the W. bdy. of sec. 29.
	At point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a porphyry rock, 3x6x9 ins., mkd. X, deposited at base of post, for the closing cor. of secs. 30 and 31, with brass cap mkd.