

1320

## COMPLETION OF THE SURVEY OF THE SUBDIVISIONS OF T. 16 N., R. 47 E.

Chains

16.40

Draw, drains N. 70° E.

36.63

Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, with limestone, 3x4x5 ins., mkd. X, deposited at the base, and in a large mound of stone to top of post, for  $\frac{1}{4}$  sec. cor. of sec. 18 only, with brass cap mkd.

 $\frac{1}{4}$  S 18

1937

from which

A 4 in. X on top surface of granite outcrop, bears N. 49° E., 17 lks. dist.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 19 only, with brass cap mkd.

 $\frac{1}{4}$  S 19

1937

from which

A pinon pine, 14 in. diam., bears S. 60° W., 97 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

A pinon pine, 16 ins. diam., bears N. 58 $\frac{1}{2}$ ° W., 118 lks. dist., mkd. BT only.

Continue descent of rolling E. slope.

44.00

Leave scattering timber; continue through scattering undergrowth.

73.50

Intersect W. bdy. of sec. 17.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a granite rock, 2x6x6 ins., mkd. X, deposited at the base of post, for the closing cor. of secs. 18 and 19, with brass cap mkd.

	T16N	
	S18	
CC	—	S17
	S19	
	R47E	

1937

From this closing cor., the cor. of secs. 17 and 20, hereinbefore described, bears S. 3° 28' W., 2.29 chs. dist.

Land, rolling.

Soil, gravelly to rocky clay loam; 2nd and 3rd rate.

Undergrowth, sagebrush, buck brush, shadscale.

Timber, juniper and pinon pine.

Grazing, fair.

## GENERAL DESCRIPTION

Sections 18, 19, 30 and 31, which were omitted from the original