1. 1.

Chains

Beginning at the original standard cor. of Tps. 16 N., Rs. 47 and 48 E., which is an eroded weatherbeaten cottonwood post, 3 ins. sq., 3 ft. long, loosely set in a mound of earth and stone, with markings illegible. All traces of pits have disappeared.

At point for cor,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with a limestone, 5x4x2 ins., mkd. X, and the original post deposited at the base, for standard cor. of Tps. 16 N., Rs. 47 and 48 E.

S C T 16 N R47E R48E S36 S31

raise a mound

of stone, 2 ft. base, 12 ft. high, N. of cor.

S. 89° 02' E., with the establishment of the third standard parallel north, along the S. bdy. of sec. 31, T. 16 N., R. 48 E., on a solar line.

Over gently rolling valley floor, asc. 75 ft. over W. slope, through dense undergrowth.

40.00

Departure of 40.00 chs. easting; intersect the original standard \$\frac{1}{2}\$ sec. cor., which is a conglomerate stone, \$16x10x\frac{1}{2}\$ ins., firmly set in ground, mkd. \$\frac{1}{4}\$ on N. face. All indications of the pits have disappeared.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone, deposited at the base, for standard \(\frac{1}{4} \) sec. cor., with brass cap mkd.

S C 1/4 S 31

1937

raise a mound

of stone, 2 ft. base, 12 ft. high, N. of cor.

Asc. gradually 70 ft. over a gently rolling W. slope.

62.22

Intersect the original closing cor. of secs. 5 and 6, T. 15 N., R. 48 E., which is an eroded weatherbeaten cottonwood post, 3 ins. sq., 3 ft. long, loosely set in a mound of earth and stone, with markings illegible.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original post, deposited at the base, for closing cor. of secs. 5 and 6, T. 15 N., R. 48 E., with brass cap mkd.

T16N R48E

S31

T15N R48E

CC

raise a mound

of stone, 2 ft. base, 12 ft. high, S. of cor.

Asc. 60 ft. over a gently rolling W. slope.

80.01 Departure of 80.00 chs. easting; intersect the original standard cor.