

THIRD STANDARD PARALLEL NORTH, ALONG THE S. BDY. OF  
T. 16 N., R. 48 E.

01841

Chains

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a limestone, 6x6x5 ins., mkd. X, deposited at the base, and in a mound of stone to top, for standard cor. of secs. 35 and 36.

S C  
T16N | R48E  
S35 | S36

1937

from which

A pinon pine, 5 ins. diam., bears N. 60 $\frac{1}{4}$ ° W., 22 lks. dist., mkd. T 16 N R 48 E S 35 S C B T.

A pinon pine, 4 ins. diam., bears N. 41 $\frac{1}{4}$ ° E., 18 lks. dist., mkd. T 16 N R 48 E S 36 S C B T.

Land, mountainous.

Soil, sandy, gravelly and rocky; 3rd rate.

Timber, pinon pine and juniper; undergrowth, sagebrush, and a fair growth of grass.

East, along the S. bdy. of sec. 36, on a solar transit line.

Over mountainous land, through scattering timber and dense undergrowth, desc. 80 ft.

2.40 Wash, course NW.; asc. 65 ft.

10.40 Top of spur, projects N.; desc. 5 ft.

13.00 Hillside drain, course N. 10 lks. to junction with large wash, which drains N. 60° W.; asc. 30 ft.

15.70 Point of crag jutting N.; desc. 10 ft.

17.10 Bottom of same wash, course N. 75° W.; asc. 115 ft.

30.00 Top of spur, slopes S.; desc. 10 ft.

33.50 Wash, course S. 65° W.; asc. 40 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
 $\frac{1}{4}$  S 36

1937

from which

A juniper, 6 ins. diam., bears N. 25° W., 17 $\frac{1}{4}$  lks. dist., mkd.  $\frac{1}{4}$  S 36 S C B T.

A juniper, 3 ins. diam., bears N. 22 $\frac{1}{4}$ ° E., 67 lks. dist., mkd. B T only.

Asc. 115 ft. over rocky W. slope.

49.80 Hillside drain, course NW.; asc. 130 ft. over W. slope.

57.00 Top of spur, slopes N. 20° W.; desc. 10 ft.

59.90 Hillside drain, course NW.; asc. 70 ft.

65.10 Hillside drain, course N. 60° W.; asc. 280 ft.