

INDEPENDENT RESURVEY OF THE  
EAST BOUNDARY OF T. 16 N., R. 48 E.

347

## Chains

mkd. T 17 N R 48 E S 36 B T.

A mahogany, 5 ins. diam., bears S. 43° W., 88 lks. dist.,  
mkd. T 16 N R 48 E S 1 B T.

Land, mountainous.

Soil, sandy, gravelly and rocky; 3rd rate.

Timber, juniper, pinon pine and mahogany; undergrowth, sagebrush and  
a fair growth of grass.

Dependent Resurvey of the East Boundary of T. 16 N., R. 47 E.

Reestablishment of the surveys executed by Don H. Barker, U. S.  
Deputy Surveyor, in 1874.

Beginning at the reestablished standard cor. of Tps. 16 N., Rs. 47 and  
48 E., heretofore described.

N. 1° 03' E., on a true line, along the E. bdy. of sec. 36 T. 16 N.,  
R. 47 E.

Over gently rolling valley floor, desc. 10 ft. over W. slope, through  
dense undergrowth.

8.00 Wash, course N. 52° W.; asc. 15 ft.

19.00 Top of low broad spur, slopes W.; desc. 15 ft.

23.30 Wash, course W.; asc. 15 ft.

39.95 Intersect evident remains of the original  $\frac{1}{4}$  sec. cor., which is a  
portion of eroded granite stone forming a small mound, all markings  
having been destroyed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,  
for  $\frac{1}{4}$  sec. cor., for sec. 36 only, with brass cap mkd.

$\frac{1}{4}$  S 36

1937

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Orig. stone deposited at base of post.

Thence

N. 1° 00' E.

Desc. 10 ft.

15.00 Wash, course S. 80° W.; asc. 10 ft.

24.00 Top of low broad spur, slopes W.; desc. 15 ft.

30.15 Wash, course N. 70° W.; asc. 10 ft.

39.85 Intersect the original cor. of secs. 25, 30, 31 and 36, which is  
granite stone, 7x5x3 ins., weatherbeaten and partly eroded, with  
1 groove on S. side discernable, no other marks visible.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,  
with the original stone deposited at the base, for cor. of secs. 25  
and 36 only, with brass cap mkd.