

SUBDIVISION OF T. 16 N., R. 48 E.

335

408

Chains

Desc. 10 ft. over a W. slope.

43.80 Drain, course NW.; desc. 45 ft. over a W. slope.

57.40 Drain, course N. 20° W.; desc. 25 ft. over a W. slope.

78.37 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 30 and 31, with brass cap mkd.

T16N	T16N
R47E	S30
	S31
S36	R48E

1939

raise a mound
of stone, 2 ft. base, 1½ ft. high, E. of cor.

From this point the cor. of secs. 25 and 36, T. 16 N., R. 47 E., hereinbefore described, bears N. 1° 00' E., 115 lks. dist.

Land, rolling.

Soil, sandy, gravelly clay, 3d rate.

No timber; undergrowth, shadscale, sagebrush and rabbitbrush.

Grazing, good.

At a point 40.00 chs. dist. from the closing cor. of secs. 30 and 31, on the E. bdy. of sec. 36, T. 16 N., R. 47 E.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the ¼ sec. cor. of sec. 31, with brass cap mkd.

¼ S 31

1939

raise a mound
of stone, 2 ft. base, 1½ ft. high, E. of cor.

The ¼ sec. cor. of sec. 36, on the E. bdy. of T. 16 N., R. 47 E., hereinbefore described, bears N. 1° 03' E., 1.30 chs. dist.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Asc. slightly over rolling land, along a W. slope, thru scattering undergrowth.

33.00 Drain, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quart of charcoal deposited at base, for the ¼ sec. cor., with brass cap mkd.

¼
S30 S29

1939

Desc. 45 ft. along a W. slope.

55.70 Drain, course W.; enter scattering timber; asc. 20 ft.

66.70 Wash, course W.; asc. 10 ft. along a W. slope.