

SUBDIVISION OF T. 16 N., R. 48 E.

Chains

with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 19
 $\frac{1}{4}$ S 30
1939

Desc. 85 ft. over a W. slope.

50.00 Leave scattering timber.

63.60 Drain, course W.; desc. 40 ft. over a W. slope.

76.83 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a quart of charcoal deposited at base, for the closing cor. of secs. 19 and 30, with brass cap mkd.

T16N	T16N	
R47E	S19	
	S30	CC
S25	R48E	

1939

From this point the cor. of secs. 24 and 25, T. 16 N., R. 47 E., hereinbefore described, bears N. $0^{\circ} 58'$ E., 60 lks. dist.

Land, rolling.

Soil, gravelly sandy clay, 3d rate.

Timber, juniper; undergrowth, sagebrush, shadscale and rabbitbrush.

Grazing, poor.

At a point midway bet. the closing cors. of secs. 19 and 30, and 30 and 31, on the E. bdy. of T. 16 N., R. 47 E.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor. of sec. 30, with brass cap mkd.

$\frac{1}{4}$ S 30
1939

From this point the $\frac{1}{4}$ sec. cor. of sec. 25, T. 16 N., R. 47 E., hereinbefore described, bears N. $1^{\circ} 04'$ E., 85 lks. dist.

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ} 03'$ W., bet. secs. 19 and 20:

Desc. 5 ft. over rolling land, along a W. slope, thru scattering timber and undergrowth.

3.50 Drain, course W.; asc. 15 ft. over a S. slope.

6.00 Spur, slopes W.; desc. 45 ft. over a N. slope.

9.00 Wash, course W.

16.30 Drain, course W.

19.40 Drain, course W.