

460

SUBDIVISION OF T. 16 N., R. 49 E.

Chains

A pinon pine, 8 ins. diam., bears S. 75° E., 34 lks. dist., mkd. 1/4 S 11 B T.

A pinon pine, 8 ins. diam., bears N. 37° W., 55 lks. dist., mkd. 1/4 S 2 B T.

53.40 Top of spur, slopes SE.; asc. 10 ft.

58.40 Head of drain, course SE.; asc. 90 ft.

66.80 Point of spur, slopes SE.; desc. 5 ft.

70.70 Head of hillside drain, course SE.; asc. 250 ft.

80.08 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous.

Soil, sandy, shallow, gravelly and rocky; 3rd rate.

Timber, juniper, pinon pine and mahogany; undergrowth, sagebrush, buckbrush and a fair growth of grass.


N. 0° 01' W., bet. secs. 2 and 3.

Over mountainous land, through scattering timber and dense undergrowth, desc. 10 ft.

5.00 Head of hillside drain, course SE.; asc. 90 ft.

13.00 Top of spur, projects E. 1.00 ch.; thence SE.; desc. 325 ft. over NE. broken slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



raise a mound

of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.


40.40 Head of wash, 20 ft. below 1/4 sec. cor., course E.; asc. 30 ft.

43.50 Top of spur, slopes SE.; desc. 150 ft. over broken E. slope.

56.80 Ravine, course S. 50° E.; asc. 370 ft. over SE. slope.

75.37 Intersect the S. bdy. of T. 17 N., R. 49 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.



raise a mound

of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

From point of intersection the cor. of secs. 34 and 35, on the S. bdy. of T. 17 N., R. 49 E. bears West, 6.18 chs. dist., previously described.

Land, mountainous.

Soil, sandy, shallow, gravelly and rocky; 4th rate.