

468

SUBDIVISION OF T. 16 N., R. 49 E.

Chains	S. 89° 58' E., on a random line, bet. secs. 3 and 10.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect N. and S. line, 7 lks. S. of cor. of secs. 2, 3, 10, and 11.
	Thence
	S. 89° 59' W., on true line bet. secs. 3 and 10.
	Over mountainous land, through scattering timber and dense undergrowth, asc. 390 ft. over rocky E. slope.
20.00	Top of divide ridge, bears N. and S.; asc. 60 ft. over a general S. slope.
35.00	Head of ravine, course S.; asc. 5 ft.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S \ 3 \\ \hline S \ 10 \\ 1939 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Asc. 285 ft. along S. slope.
70.00	Top of spur ridge, bears NE. and SW.; desc. 40 ft. over W. slope.
80.08	The cor. of secs. 3, 4, 9, and 10.
	Land, mountainous.
	Soil, sandy, shallow, gravelly and very rocky; 4th rate.
	Timber, scattering scrub juniper, pinon pine, mahogany and scrub aspen; undergrowth, sagebrush, buckbrush and a fair growth of grass.
	N. 0° 02' W., bet. secs. 3 and 4.
	Over mountainous land, through scattering scrub juniper, pinon, mahogany and aspen timber and dense undergrowth, asc. 10 ft. over W. slope.
5.00	Top of spur, projects W.; desc. 175 ft. over NW. slope.
26.80	Ravine, course S. 50° W.; asc. 225 ft. over a general S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ S4 \quad \quad S3 \\ 1939 \end{array}$
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Asc. 300 ft. over a general S. slope.
59.70	Top of spur, projects SW.; asc. 60 ft. over W. slope.
75.25	Intersect the S. bdy. of T. 17 N., R. 49 E.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3, and 4, with brass cap mkd.