

SUBDIVISION OF T. 16 N., R. 49 E.

Chains

$\frac{1}{4}$   
 S5 | S4  
 1939

from which

A juniper, 4 ins. diam., bears N.  $62\frac{1}{2}^{\circ}$  E., 33 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

A pinon pine, 6 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  W., 316 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

Asc. 80 ft. over SW. slope.

46.80 Point of spur, projects W.; desc. 125 ft.

60.50 Ravine, course S.  $60^{\circ}$  W.; asc. 40 ft. to cor.

67.70 Dim unimproved road, bears N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W.

75.19 Intersect the S. bdy. of T. 17 N., R. 49 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.

T17N R49E  
 S33  


---

 S5 | S4  
 T16N | R49E  
 .CC  
 1939

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$ -ft. high, S. of cor.

From point of intersection the cor. of secs. 32 and 33, on the S. bdy. of T. 17 N., R. 49 E., bears West, 5.98 chs. dist., previously described.

Land, mountainous.

Soil, sandy, shallow, gravelly and rocky; 4th rate.

Timber, scrub juniper, pinon pine and mahogany; undergrowth, sage-brush and a fair growth of grass.

At midpoint bet. the closing cors. on the N. bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a limestone, 6x5x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., for secs. 4 only, with brass cap mkd.

$\frac{1}{4}$  S 4  
 1939

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

From this cor., the  $\frac{1}{4}$  sec. cor., for sec. 33, on the S. bdy. of T. 17 N., R. 49 E.; bears West, 6.02 chs. dist., heretofore described.

From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., heretofore described.

N.  $0^{\circ} 03' W.$ , bet. secs. 31 and 32.