

490

SUBDIVISION OF T. 16 N., R. 49 E.

Chains

bedrock, with a granite stone, 8x5x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

S 5
1/4
S 8
1939

- 46.80 Dim unimproved road, bears N. 30° E. and S. 30° W.
- 49.00 Ravine, course S. 30° W.; asc. 115 ft. over broken SE. slope.
- 77.40 Top of spur, slopes S.; desc. 10 ft.
- 79.98 The cor. of secs. 5, 6, 7 and 8.

Land, mountainous.
Soil, sandy, gravelly and rocky; 3rd rate.
Timber, juniper, pinon pine and mahogany; undergrowth, sagebrush and a fine growth of grass.

West, on true line bet. secs. 6 and 7.

Over mountainous land, through scattering timber and dense undergrowth, desc. 60 ft. over SW. slope.

- 7.50 Ravine, course S.; asc. 140 ft. over broken SE. slope.
- 24.70 Point of spur, projects S. 30° W.; desc. 170 ft. over broken SW. slope.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a granite stone, 6x5x4 ins., mkd. X, deposited at the base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.

S 6
1/4
S 7
1939

from which

A juniper, 8 ins. diam., bears N. 71 1/4° W., 62 lks. dist., mkd. 1/4 S 6 B T.

A forked juniper, 6 ins. diam., bears S. 31 1/4° W., 66 lks. dist., mkd. 1/4 S 7 B T.

- 43.20 Ravine, 40 ft. below 1/4 sec. cor., course S. 30° W.; asc. 30 ft. over SE. slope.
- 47.60 Point of spur, slopes S. 30° W.; desc. 120 ft. over SW. slope.
- 77.03 Intersect the E. bdy. of T. 17 N., R. 48 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.

T16N
T17N | S6
R48E | S7 — CC
S 25 | R49E
1939

of stone, 2 ft. base, 1 1/2 ft. high, E. of cor. raise a mound