

DEPENDENT RESURVEY OF W. BDY. T. 1 S., R. 35 E.

Chains

REESTABLISHMENT OF SURVEYS EXECUTED BY
HATCH, BARKER, AND EATON, DEPUTY
SURVEYORS, IN 1877.

Beginning at the cor. of secs. 19, 24, 25, and 30, on the
W. bdy. of the Tp., which is a granite stone, 16x11x10
ins. above ground, firmly set, mkd. as described in the
official record. All traces of pits have disappeared.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in
the ground to bed rock, with the original granite stone
deposited alongside post, and in a mound of stone to top,
for cor. of secs. 19, 24, 25, and 30, with brass cap mkd.

T1S

R34E R35E

S24 | S19

S25 | S30

1937

raise a mound
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Thence

N. 0° 14' E., along the W. bdy. of sec. 19.

Asc. gradually over a rolling, broken E. slope; surface
strewn with loose boulders and covered with scrub under-
growth.

9.90 Channel of dry gravel wash, 20 lks. wide, course E.;
asc. 20 ft.

20.40 Spur, projects E.; desc. 20 ft. to ¼ sec. cor.

22.80 Dry shallow gravel wash, 30 lks. wide, course E.

39.30½ Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for ¼ sec. cor., for sec. 19, with brass cap mkd.

¼ S19

1937

raise a mound
of stone, 2 ft. base, 1½ ft. high, E. of cor.

39.60 Dry wash, course E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for ¼ sec. cor. for sec. 24, with brass cap mkd.

¼ S24

1937

raise a mound
of stone, 2 ft. base, 1½ ft. high, W. of cor.

40.80 Dim wagon road, bears E. and W.; on top of low spur,
sloping E.; desc. 10 ft.

47.60 Dry shallow wash, course N. 50° E.; desc. 10 ft.

60.65 Dry gravel wash, course E.; desc. 10 ft.