

DEPENDENT RESURVEY OF SUBDIVISION LINES T. 1 S., R. 34 E.

Chains

desc. 240 ft. over rocky NW. slope.

74.86

The cor. of secs. 18 and 19, on the W. bdy. of the Tp. heretofore described.

Land, rolling mountainous and mountainous. Soil, light sandy shallow on rocky clay and decomposed granite base, with much loose rock on surface; 4th rate. Timber, pine and juniper; undergrowth, sagebrush, shadscale, greasewood and a fair growth of grass.

SUBDIVISION OF T. 1 S., R. 34 E.

From the cor. of secs. 23, 24, 25, and 26, heretofore described;

North, bet. secs. 23, and 24, on a sectional guide meridian.

Over rolling mountainous land, through scattering undergrowth, asc. gradually 30 ft. over SE. slope to  $\frac{1}{4}$  sec. cor.

8.20

Dry gravel wash, shallow, 15 lks. wide, course E.

17.90

Gravel wash, 10 lks. wide, course E.

33.00

Rocky wash, 40 lks. wide, 3 ft. deep, course N. 80° E.

39.71

Point for  $\frac{1}{4}$  sec. cor., which is 40.00 chs. latitudinal distance from the cor. of secs. 13, 14, 23, and 24, hereinafter determined.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S23|S24

1937

raise a mound of stone, 40 ft. base, 3 ft. high, W. of cor.

Desc. 20 ft.

44.30

Wash, 10 lks. wide, course E.

51.60

Gulch, channel 1.00 ch. wide, with sloping banks 5 ft. high, course N. 75° E.; asc. 40 ft. over rocky S. slope.

53.30

Top of low broad spur, slopes E.; desc. 50 ft.

60.70

Dry wash, course E.; asc. 330 ft.

79.10

Top of rocky spur ridge, projects E.; desc. 30 ft.

79.71

Point, for cor. of secs. 13, 14, 23, and 24, which is 80.46 chs. West of the cor. of secs. 13 and 24, on the E. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 13 ins. in the ground to bed rock; with a granite stone, 4x3x2 ins., mkd. X, deposited at the base, and in a mound of stone to top, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.