SUBDIVISION OF T. 1 S., R. 34 E.

Chains	
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
40.90	Head of wash, course S. 30° E.; asc. 40 ft.
46.10	Top of ridge, bears N. 80° W. and S. 80° E.; desc. 100 ft.
51.80	Head of wash, course N. 55° E.; asc. 60 ft.
56.10	Point of spur, slopes E.; desc. 170 ft.
63.00	Gulch, from S. 80° W., course S. 65° E.; asc. 80 ft.
66.40	Top of spur, slopes S. 80° E.; desc. 10 ft.
67.50	Wash, course N. 75° E.; asc. 60 ft.
71.50	Top of spur, slopes E. 8.00 chs. dist.; thence S. 60° E.; desc. 160 ft.
78.70	Ravine, course S. 70° E.; asc.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the cor. of lots 1 and 8 of sec. 5, and lots 4 and 5 of sec. 4, with brass cap mkd: 1 | 4 S5 — S4 8 | 5 1939
83.60	Ravine, course S. 40° E.; asc. 100 ft.
85.92	Intersect the Mount Diablo Base line, the N. bdy. of Tp.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd. T1N R34E S32 S 5 | S 4 T1S R34E C C 1937
	raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
	From point of intersection the standard ¼ sec. cor. S. bdy. sec. 32, T. 1 N., R. 34 E., bears W. 3.97 chs. dist.; an iron post, 1 in. diam., firmly set in a mound of stone, mkd. as described in the official record.
	From the same point the standard cor. of secs. 32 and 33, S. bdy. T. 1 N., R. 34 E., bears E. 36.03 chs. dist.; an iron post, 2 ins. diam., 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.
	Land, rolling mountainous. Soil, shallow sand and rocky clay, on a granite base; with much loose rock on surface; 4th rate. No timber; undergrowth, sagebrush, shadscale, greasewood and a fair growth of grass.
	At midpoint bet. the closing cors. on the N. bdy. sec. 4.