

DEPENDENT RESURVEY OF THE S. BDY. OF T. 9 N., R. 31 E.

Chains

T. 8 N., R. 31 E., which is an iron post, 1 in. diam., firmly set, properly mkd. and witnessed as described in the official record.

N. 89°40' E., 3.05 chs.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 33, T. 9 N., R. 31 E., with brass cap mkd.

$\frac{1}{4}$ S33

1934

18x18x12 ins., E. and W. of the cor., 3 ft. dist. dig pits,

From the cor. of secs. 4 and 5, on the N. bdy. of T. 8 N., R. 31 E., which is an iron post, 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record.

N. 88°34' E., 3.22 chs.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 32 and 33, T. 9 N., R. 31 E., with brass cap mkd.

T9NR31E

S32 S33

1934

of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of the cor. raise a mound

From the $\frac{1}{4}$ sec. cor. of sec. 5 on the N. bdy. of T. 8 N., R. 31 E., which is an iron post, 1 in. diam., firmly set, properly mkd. and witnessed as described in the official record.

N. 89°37' E., 3.70 chs.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 32, T. 9 N., R. 31 E., with brass cap mkd.

$\frac{1}{4}$ S32

1934

of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of the cor. raise a mound

INDEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 9 N., R. 31 E.

Independent resurvey, superceding the survey by Conkling and Stewart, U. S. Deputy Surveyors, in 1883, Contract No. 165.

Beginning at the cor. of Tps. 8 and 9 N., Rs. 31 and 32 E., which is an iron post, 3 ins. diam., firmly set, properly mkd. and witnessed as described in the official record, Group 171 Nevada.