	Chains 40.00	North 17 lks. from the tangent,
	with the second	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, and in a mound of stone, for the 4 sec. cor., with brass cap mkd.
	*> =	\$32 \frac{1}{4} \frac{\$5}{}
		1934
	SURFICIEUX II	Deposit a basalt stone, 2x3x5 ins., mkd. with a cross (X) at base of the post.
	Jan and	This cor. is situated on a large spur projecting S:10° W.
		Desc. 300 ft. over a W. slope.
	53.80	Head of draw, drains S.; desc. 10 ft. along a SW. slope.
	69.70	Ridge, bears NE. and SW.; desc. 45 ft. over a NW. slope.
	80.00	North 20 1ks. from the tangent,
		Set an iron post, 3 ft. long, 2 ins. diam., over a cross (X) cut into solid rock, and supported by a large mound of stone, for the cor. of secs. 5, 6, 31, and 32, with brass cap mkd.
0		TIONR31E
		\$31 \ \$32 \$6 \ \$5
		T9N 1934
	and the second	Deposit a basalt stone, 2x3x4 ins., mkd. with a cross (X) at base of the post.
		This cor. is situated at the edge of scattered juniper timber.
		Land, rough mountainous. Soil, rocky, clay loam; 4th rate. Undergrowth, shadscale and squawbrush.
		Timber, scattering juniper. Grazing, poor.
T.	or on a secondary	
1000000	11113	
100	. e	West, bet. secs. 6 and 31 on a transit line describing the tangent, which bears S. 89°56.5' W.
		Over rough mountainous land, through scattering undergrowth; desc. 455 ft. over a NW. slope.
2000	13.10	Draw, drains NW.; asc. 210 ft. over a NE. slope.
	25.40	Ridge, bears NW. and SE.; desc. 600 ft. over a SW. slope to the 45.50 ch. point.
	70.00	Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground to solid rock, and supported by a large mound of stone; for the # sec. cor., with brass cap mkd.