Chains 40.00

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone, for the 4 sec. cor., with brass cap mkd.

Deposit a basalt stone, 4x4x5 ins., mkd. with a cross (X) at base of the post.

82.07

Intersect the W. bdy. of the township.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to solid rock, and supported by a large mound of stone, for the closing cor. of secs. 19 and 30, T. 9 N., R. 31 E., with brass cap mkd.

Deposit a basalt stone, 2x2x2 ins., mkd. with a cross (X) at the base of the post.

From this cor. the original cor. of secs. 19, 24, 25, and 30, which is an iron post, 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record, bears South 5.66 chs. dist. This cor. now refers to R. 30 E. only, and the brass cap markings are altered to read, as follows:

Land, gently rolling.
Soil, sand; 3rd rate.
Undergrowth, greasewood. Native grasses.
Timber, none.
Grazing, poor.

N. 0903! W., bet. secs. 19 and 20.

Over gently rolling land, across numerious small washes draining W., through scattering undergrowth; asc. 300 ft. to the 80.00 ch. point.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the 4 sec. cor., with brass cap mkd.