

## SUBDIVISION OF T. 9 N., R. 31 E.

Chains	West, on true line bet. secs. 18 and 19.
	Over rolling land, through scattering undergrowth; desc. 380 ft. to the 82.01 ch. point.
2.50	Wash, drains SW. from the N.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, and supported by a large mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S18 \\ \frac{1}{4} \\ S19 \\ 1934 \end{array}$
	Deposit a basalt stone, 2x2x4 ins., mkd. with a cross (X) at the base of the post.
82.01	Intersect the W. bdy. of the township
	At point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 18, and 19, T. 9 N., R. 31 E., with brass cap mkd.
	$\begin{array}{r} T9N \\ R30E \mid R31E \\ S13 \mid S18 \\ S19 \mid CC \\ 1934 \end{array}$
	raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, E. of the cor.
	From this cor. the original cor. of secs. 13, 18, 19, and 24, which is an iron post, 2 ins. diam., firmly set, properly marked and witnessed, as described in the official record bears South 5.66 chs. dist. This cor. now refers to R. 30 E. only and the brass cap markings are altered to read, as follows:
	$\begin{array}{r} T9N \\ R30E \mid \\ S13 \mid \\ S24 \mid \\ 1917 \end{array}$
	Land, gently rolling.
	Soil, sandy to rocky clay loam; 4th rate.
	Undergrowth, greasewood.
	Timber, none.
	Grazing, poor.
	N. 0°03' W., bet. secs. 17 and 18.
	Over mountainous land, through scattering undergrowth; asc. 295 ft. along a S. slope on the E. side of a draw draining S.
25.00	Head of a draw, drains S. 50° W.; continue ascent 115 ft.