

## SUBDIVISION OF T. 9 N., R. 31 E.

Chains	
30.30	Draw, drains S. 40° W.; asc. 70 ft. over a rocky SE. slope.
36.10	Spur, projects S. 30° W.; desc. 120 ft. over a rocky SW. slope to the 40.50 ch. point.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock, and in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;">           S7  <math>\frac{1}{4}</math>            S18            1934         </div>
	Deposit a basalt stone, 3x3x3 ins., mkd. with a cross (X) at base of the post.
40.50	Draw, drains S. 20° W.; asc. 10 ft. over a SE. slope.
49.30	Spur, projects S. 45° W.; desc. 220 ft. over a steep rocky NW. slope.
52.50	Draw, drains S. 70° W.; asc. 95 ft. over a rocky SE. slope.
62.10	Spur, projects S. 30° W.; desc. 315 ft. along a general NW. slope to the 81.87 ch. point.
71.60	Large draw, drains S. 85° W.
81.87	Intersect the W. bdy. of the township.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 7 and 18, T. 9 N., R. 31 E., with brass cap mkd.

T9N  
 R30E R31E  
 S7  
 CC  
 S12 S18  
 1934

raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, E. of the cor.

From this cor. the original cor. of secs. 7, 12, 13, and 18, which is an iron post, 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record, bears South 5.76 chs. dist. This cor. now refers to R. 30 E. only and the brass cap markings are altered to read, as follows:

T9N  
 R30E  
 S12  
 S13  
 1934

Land, rough mountainous.  
 Soil, clay loam; 4th rate.  
 Undergrowth, sagebrush.  
 Timber, none.  
 Grazing, poor.