SUBDIVISION OF T. 9 N., R. 31 E.

-	Chains 47.60	Spur, projects Sw.; desc. 225 ft. over a W. slope.
	TO TO COLUMN	THE AT ALMOST BE AND ADDRESS OF A REAL OF A PROPERTY OF A SECTION OF A
	53•90	Head of a draw, drains W.; continue to desc. 350 ft. along the bottom of the draw.
	78.72	Large wash, drains SW. from the E.; asc. 10 ft.
	81.82	Intersect the W. bdy. of the township.
		At the point of intersection,
	-247 BS	Set an iron post, 3 ft. long, 2ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, for the closing cor. of secs. 6 and 7, T. 9 N., R. 31 E., with brass cap mkd.
	a	T9N
		T9N R30E R31E S6 S1 CC S7
		S1 - CC - S7
		1934
		Deposit a rhyolite, 5x6x7 ins., mkd. with a cross (X) at base of the post.
		From this cor. the original cor. of secs. 1, 6, 7, and 1
		which is an iron post, 2 ins. diam., firmly set, properl mkd. and witnessed as described in the official record
der o		bears South 5.60 chs. dist. This cor. now refers to R. 30 E. only and the brass cap markings are altered to read, as follows:
		TON
*		T9N R30E S1
		s12 1917
. 5755	res vi se	Land, rough mountainous.
		Undergrowth greasewood and sagebrish.
	75"	Timber, none.
		didzing, poor.
	S = 10	125-70 Tues Translated
		cir cools was a managem described and the second of
		N. 0004' W., on a random line bet. secs. 5 and 6.
	po•00	Set temp. 4 sec. cor.
	79.82	Intersect the N. bdy. of the township at a point 5 lks. E. of the cor. of secs. 5, 6, 31, and 32, heretofore described. Thence
		S. 0°06' E., on true line bet. secs. 5 and 6.
		Over rough mountainous land, through scattering timber and undergrowth; asc. 65 ft. along a rocky NW. slope.
	10.20	Saddle, in ridge bearing NE. and SW.; this point is at the head of two draws, one draining S. 5° E. and the other N. 4° N.; desc. 485 ft. to the 34.80 ch. point.