


4-673 D
344

SURVEY OF THE NORTH BOUNDARY OF T. 10 N., R. 30 E.

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the meander cor. of fractional secs. 6 and 31, with brass cap mkd.



raise a mound of stone, 4 ft. base, 3 ft. high, E. of the cor.

Land, gently rolling; general W. drainage.
Soil, sandy; 3rd rate.
Undergrowth, greasewood.
Grazing, poor.

SUBDIVISIONS OF T. 10 N., R. 30 E.

Beginning at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township, which is an iron post, 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record.

Thence

N. 0°01' W., bet. secs. 35 and 36.


Over mountainous land, through scattering undergrowth; asc. 400 ft. along a steep SW. slope.

15.30 Spur ridge, bears E. and W.; desc. 240 ft. along a NE. slope.

27.80 A ravine, drains N. 70° W.; continue descent 50 ft.

38.20 Small spur, projects W. about 2 chs.; desc. 50 ft. over a NW. slope to the 44.20 ch. point.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to solid rock, and in a mound of stone, for the 1/4 sec. cor., with brass cap mkd.



Deposit a granite stone, 2x4x6 ins., mkd. with a cross (X) at base of post.

44.20 Ravine, drains S. 45° W.; asc. 250 ft. along a steep SW. slope.

59.50 Spur, projects S. 65° W. from the E.; desc. 140 ft. along a steep NE. slope.

66.20 A ravine, drains W.; asc. 275 ft. along a steep SW. slope.

78.60 Spur, projects S. 30° E. from N. 40° W.; desc. 15 ft. along a steep NE. slope.