

578

SUBDIVISIONS OF T. 13 $\frac{1}{2}$ N., R. 50 E.

Chains	Over mountainous land through medium dense undergrowth and timber; asc. 120 ft. over a NE. slope.
11.70	Spur ridge, bears N. 15° E. and S. 50° W., desc. 20 ft. over NW. slope.
17.00	Drain, course N. 20° E., asc. 140 ft. over a broken NE. slope.
35.10	Main divide, bears N. 60° W. and S. 40° E., desc. 110 ft. over SW. slope.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 21 $\frac{1}{4}$ S 28 1938
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Desc. 40 ft. over SW. slope.
44.70	Draw, drains S. 15° W., asc. 350 ft. over a steep SE. slope.
59.50	Spur, slopes S. 70° W., desc. 490 ft. over a westerly slope.
79.96	The cor. of secs. 20, 21, 28 and 29.
	Land, mountainous. Soil, shallow and rocky; 4th rate. Timber, nut pine and mahogany; undergrowth, big sage and bunch grass. Grazing, good.
	N. 0° 03' W., bet. secs. 20 and 21.
	Over mountainous land through medium dense undergrowth and timber; desc. 30 ft. over NW. slope.
8.50	Dry creek channel and small spring, course S. 60° W., asc. 210 ft. over a SW. slope, leave timber.
27.00	Ridge, bears W. and S. 70° E., desc. 50 ft. over a northerly slope.
32.54	Intersect S. bdy. of T. 14 N., R. 50 E.
	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground and in a mound of stone, to top, for closing cor. of secs. 20 and 21, with brass cap mkd.
	T14N R50E S31 ----- S20 S21 T13 $\frac{1}{2}$ N CC 1938
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.
	From point of intersection, the cor. of secs. 31 and 32, T. 14 N., R. 50 E., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East 1.66 chs. dist.