

604

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF

T. 32 N., R. 33 E.

| Chains | Reestablishment of a portion of the 7th Standard Parallel North, executed by E. H. Dyer, U. S. Surveyor, in 1863. |
|--------|--|
| | <p>Beginning at the original standard cor. of secs. 32 and 33, T. 32 N., R. 33 E., which is a decayed willow stake, with marks obliterated, surrounded by a small mound of stone, all traces of pits and trench are obliterated.</p> <p>At point for cor.,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 32 and 33, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R33E</p> <p>S32 S33</p> <hr style="width: 10%; margin: 0 auto;"/> <p>1939</p> </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, 1½ ft. high, N. of cor. Deposit decayed stake alongside cor.</p> |
| | <p>Thence</p> <p>N. 89° 59' W., on true line, along S. bdy. sec. 32.</p> <p>Over rolling land, through scattering undergrowth.</p> |
| 8.90 | Improved road, bears N. 50° W. and S. 50° E. |
| 31.60 | Dry wash, course S. 60° E. |
| 40.03 | Intersect evident remains of the original ¼ sec. cor., which is a decayed stake, with marks obliterated, lying on a small mound of earth, all traces of pits and trench are obliterated. |
| | <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <p>¼ S 32</p> <hr style="width: 10%; margin: 0 auto;"/> <p>1939</p> </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, 1½ ft. high, N. of cor. Deposit decayed stake alongside cor.</p> |
| | Thence continue with line and measurement. |
| 48.10 | Dry shallow wash, drains S. 20° E. |
| 61.30 | Dry wash, drains S. 50° W. |
| 70.00 | Ungraded road, bears N. and S. |
| 80.18 | Intersect evident remains of the original cor. of secs. 31 and 32, which is a decayed stake, with marks obliterated, lying on the ground, all traces of pits and trench are obliterated. |
| | <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the decayed stake alongside, for cor. of secs. 31 and 32, only, with brass cap mkd.</p> |