

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
OF T. 32 N., R. 33 E.

Chains

Reestablishment of a portion of the W. bdy. of T. 32 N., R. 33 E., executed by E. H. Dyer, U. S. Surveyor, in 1863.

Beginning at the original cor. of secs. 19, 24, 25 and 30, T. 32 N., Rs. 32 and 33 E., which is a greatly decayed stake, 27 ins. long, $1\frac{1}{2}$ ins. sq. with scribe marks discernable but not legible, lying on the ground; all traces of pits and trench are obliterated.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the decayed stake alongside, for cor. of secs. 19, 24, 25, and 30, with brass cap mkd.

T32N	
R32E	R33E
S24	S19
<hr/>	
S25	S30
1939	

18x18x12 ins., in each sec., 3 ft. dist. dig pits,

Thence

S. $0^{\circ} 27'$ W., on true line, bet. secs. 25 and 30.

Over rolling land, through dense undergrowth.

40.32

All indications of the original cor. have disappeared.

At the proportional point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S25	S30
<hr/>	
1939	

18x18x12 ins., N. and S. of post, 3 ft. dist. dig pits,

61.30

Wash, shallow, 1.00 ch. wide, drains S. 10° E.; asc. 20 ft.

78.40

Top of sand dune, projects S. 20° W.; desc. 10 ft.

80.64

Intersect the original cor. of secs. 25, 30, 31, and 36, which is a greatly decayed stake, 32 ins. long, 2 ins. sq. with scribe marks discernable but not legible, lying on the ground; all traces of pits and trench are obliterated.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the decayed stake alongside, for cor. of secs. 25, 30, 31, and 36, with brass cap mkd.

T32N	
R32E	R33E
S25	S30
S36	S31
<hr/>	
1939	

18x18x12 ins., in each sec., 3 ft. dist. dig pits,