

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONS
OF T. 32 N., R. 33 E.

Chains	dense undergrowth.
40.08	Proportional point for the $\frac{1}{4}$ sec. cor., Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> S19 $\frac{1}{4}$ S30 1939 </div> <div style="text-align: right;">raise a mound</div> of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
42.00	Ungraded road, bears N. 25° E. and S. 15° W.
67.80	Graded road, bears N. 23° W. and S. 15° E.
80.03	Intersect the cor. of secs. 19, 24, 25, and 30, on the W. bdy. Land, rolling. Soil, adobe mixed with sand and clay; 3rd rate. Timber, none; undergrowth, greasewood and sagebrush.

From the true point for cor. of secs. 19, 20, 29, and 30, the cor. of secs. 5, 6, 31, and 32, on the N. bdy., bears N. 0° 18' 37" W., 321.43 chs. dist.; a decayed stake, $1\frac{1}{2}$ ft. long, $\frac{3}{4}$ ins. sq. mkd. indistinctly with Roman numerals and scribe markings but not legible, all traces of pits and trench are obliterated.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a quart of broken glass deposited at base, and with the decayed stake alongside, for cor. of secs. 5, 6, 31, and 32, with brass cap mkd.

T33N R33E

S31 | S32

S6 | S5

T32N

1939

No other suitable accessory.

GENERAL DESCRIPTION

The land in sec. 30 and secs. 31 and 32 is a gently rolling plateau, with elevation 4120 to 4150 ft. above sea level. Soil, adobe mixed with sand and clay, mostly free from rocks. A large part of sec. 30, and a part of the NE. $\frac{1}{4}$ of sec. 31 and the NW. $\frac{1}{4}$ of sec. 32, is now covered by water of the Humboldt Reservoir. All drainage is to the SW. toward Humboldt River. The land area is covered with a dense to scattering growth of greasewood and sagebrush and of very little value to grazing or farming. A large earth dam with connecting levee extends through sec. 30 and part of sec. 31.