

INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL
FROM Tps. 16 NORTH, THROUGH RANGE 29 EAST

Chains	Soil, sandy and rocky, 4th rate. No timber; undergrowth, shadscale, greasewood and rabbit brush. Grazing, poor.
	West, along S. bdy. of sec. 31, on a transit line describing the secant, which bears S. 89° 58.6' W.
	Over broken mountainous land through medium dense undergrowth, desc. SW. slope.
3.90	Wash, course SE., asc. 220 ft. over E. slope.
25.60	Draw, drains S. 80° E., asc. NE. slope 80 ft.
27.80	End of spur, slopes from S. 30° W., asc. 310 ft. over steep SE. slope.
40.00	N. 2 lks. from the secant, Set an iron post, 3 ft. long, 2 in. diam., 6 ins. in the ground and in a mound of stone to top, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<p style="text-align: center;">SC $\frac{1}{4}$ S 31 1937</p> <p>From this cor., the original standard $\frac{1}{4}$ sec. cor., bears S. 12° 00' W., 7.71 chs. dist., a volcanic stone 6x10x16 ins., set 8 ins. in the ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone N. of cor.</p>
	<p style="text-align: center;">SC $\frac{1}{4}$ S 31 1937</p> <p>From this cor., the original standard $\frac{1}{4}$ sec. cor., bears S. 12° 00' W., 7.71 chs. dist., a volcanic stone 6x10x16 ins., set 8 ins. in the ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone N. of cor.</p>
	<p style="text-align: center;">SC $\frac{1}{4}$ S 31 1937</p> <p>From this cor., the original standard $\frac{1}{4}$ sec. cor., bears S. 12° 00' W., 7.71 chs. dist., a volcanic stone 6x10x16 ins., set 8 ins. in the ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone N. of cor.</p>
51.10	Black rocky spur, slopes N. 10° E., desc. W. slope.
55.90	Head of draw, 2 chs. N. of saddle, drains N., desc. 30 ft. along N. slope.
62.10	Spur ridge, bears N. and SE., desc. W. slope.
66.00	Draw, drains S., asc. 160 ft. over E. slope.
78.00	Spur, slopes N. 20° E., desc. NW. slope to cor.
80.00	N. 4 lks. from the secant, Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the standard cor. of Tps. 16 N., Rs. 28 and 29 E., with brass cap mkd.
	<p style="text-align: center;">SC T16N R28E R29E S36 S31 1937</p> <p>raise a mound of stone, 3 ft. base and 2 ft. high, N. of cor.</p>
	<p style="text-align: center;">SC T16N R28E R29E S36 S31 1937</p> <p>From this cor., the original standard Tp. cor., bears S. 12° 45' W., 7.94 chs. dist., a trap stone 8x8x12 ins. set 8 ins. in the ground, mkd. SC 16 N on N., R28E on E. and R29E on W. faces, with a mound of stone N. of cor.</p>