

INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL
TAKEN ON NORTH, THROUGH RANGE 28 EAST

Chains

69.60 Ridge, bears NW. and S. 10° W., 10 chs. to saddle, desc. 110 ft. over NW. slope to sec. cor.

80.00 On the secant,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard cor. of secs. 31 and 32, with brass cap mkd.

SC

T16N R28E

S31 S32

1937

raise a mound of stone, 2 ft. base and $1\frac{1}{2}$ ft. high, N. of cor.

From this cor., the original standard sec. cor., bears S. $11^{\circ}12'$ W., 10.37 chs. dist.; a volcanic stone 2x2 ft. x14 ins., in place, mkd. by a X, for true point, with 5 grooves E. of X, 1 groove W. of X, and SC on N. face.

I destroy the original standard sec. cor., by defacing all mks. on the stone.

Land, rolling and mountainous.

Soil, rocky; 4th rate.

No timber; undergrowth, shadscale, rabbit brush and greasewood.

Grazing, poor.

West, along S. bdy. of sec. 31, on a transit line describing the secant, which bears S. $89^{\circ}58.6'$ W.

Over rolling mountainous land through scattered undergrowth, desc. 20 ft. over SW. slope.

Wash, course S. 30° W., asc. 90 ft. over NE. slope.

Ridge, bears N. 10° E. and S. 20° W., desc. 170 ft. over broken NW. slope to $\frac{1}{4}$ sec. cor.

Spur, slopes N., continue to desc. NW. slope.

N. 2 lks. from the secant,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, with a rock 3x5x6 ins., mkd. X, deposited at the base and in a mound of stone to top, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

SC

 $\frac{1}{4}$ S 31

1937

From this cor., the original standard $\frac{1}{4}$ sec. cor., bears S. $10^{\circ}22'$ W., 10.75 chs. dist.; a volcanic stone 5x5x18 ins., set 7 ins. in the ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone N. of cor.

I destroy the original standard $\frac{1}{4}$ sec. cor.

Asc. 60 ft. along NE. slope.

Over N. slope of knoll, the summit of which is 4 chs. S.

Desc. 110 ft. over NW. slope of knoll.