

RESURVEY OF A PORTION OF SUBDIVISION OF T. 14 N., R. 28 E.

- Chains
36.70 Draw, drains S. 70° W., asc. S. slope.
- 39.93 The cor. of secs. 2, 3, 10 and 11; a basalt stone 5x8x11 ins. above ground, firmly set, mkd. and witnessed as described in the official record.
- At point for cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with original stone deposited at the base, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
- | | |
|------|------|
| T14N | R28E |
| S 3 | S 2 |
| S10 | S11 |
- 1937
- Rebuild mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- Land, rolling and mountainous.
Soil, sandy and rocky; 4th rate.
No timber; undergrowth, shadscale and black brush.
Grazing, poor.
-
- N. 0° 04' W., bet. secs. 2 and 3.
- Over mountainous land through scattered undergrowth, asc. S. slope 330 ft.
- 17.30 Ridge, bears N. 70° E., desc. along NW. slope 160 ft.
- 39.77 Proportionate distance; there is no remaining evidence of original cor.
- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- | |
|---------------|
| $\frac{1}{4}$ |
| S3 S2 |
| 1937 |
- raise a mound
- of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
- Continue over mountainous land.
- 41.70 Draw, drains SW., asc. SE. slope 240 ft.
- 56.20 Rocky ridge, bears NE. and SW., desc. NW. slope 140 ft.
- 61.30 Steep gorge, course SW., asc. broken SE. slope 80 ft.
- 68.90 Spur, slopes SW., desc. NW. slope 60 ft.
- 71.30 Ravine, course S. 30° W., asc. steep SE. slope 170 ft. to cor.
- 79.79 Intersect N. bdy. of Tp. at the cor. of secs. 2, 3, 34 and 35, a 2 in. iron post, 3 ft. long, firmly set, mkd. and witnessed as described in the field notes of T. 15 N., R. 28 E., book "S" executed under this group.
- Land, mountainous.
Soil, sandy and rocky, 4th rate.
No timber; undergrowth, shadscale and sand grass.
Grazing, poor.