DEPENDENT RESURVEY OF NORTH BOUNDARY T. 14 N., R. 28 E. Chains "Reestablishment of the surveys executed by H. E. Franks and J. S. Mullen, Deputy Surveyors, in 1904". From the cor. of secs. 2, 3, 34 and 35, N. 89° 58' W., along N. Bdy. of sec. 3, east half mile. Over broken mountainous land through scattered undergrowth, desc. 330 ft. over steep NW. slope. Ravine, course S. 6 chs. to junction with another ravine, asc. 60 ft. 13.30 along E. slope. Spur, slopes S., desc. W. slope. 20.30 Ravine, course S., asc. E. slope 180 ft. 23.70 38.61 The point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, which is mkd. by the original cor. stone, a basalt rock 6x10x16 ins., set 8 ins. in the ground and mkd. as follows: \(\frac{1}{4} \) on N. face, with mound of stone, 2 ft. base and 1 ft. high, N. of cor. At the point for cor. Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, with original cor. stone deposited at the base, and with a lava rock 3x3x5 ins., mkd. X, deposited at the base and in a mound of stone to top of iron post, for the 4 sec. cor. of sec. 3 only, with brass cap mkd. ± S 3 1937 N. 89° 55' W., along N. bdy. of sec. 3, W. half mile. Over mountainous land, asc. E. slope. A point 40.00 chs. in departure from the cor. of secs. 2, 3, 34 and 35. 1.39 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, with lava rock 4x5x6 ins., mkd. X, deposited at the base, and in a mound of stone to top, for 4 sec. cor. of sec. 34 only, with brass cap mkd. 2.60 High ridge, bears N. and S., desc. 450 ft. over broken W. slope. Ravine, course N. 80° W., continue to desc. 16.30 18.00 Spur, slopes NW. Canyon, drains S. 70° W., asc. 230 ft. over E. slope. 26.60 The point for cor. of secs. 3, 4, 33, and 34, which is mkd. by the original cor. stone, a granite rock 6x8x14 ins., set 8 ins. in the ground and mkd. as follows: 3 notches on W. and 3 notches on E. edge, 40.52 with mound of stone 2 ft. base and 15 ft. high, W. of cor.

with original cor. stone deposited at base, and in a mound of stone to top, for cor. of secs. 3 and 4 only, with brass cap mkd.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground

At point for cor.